

world of cooking

The new **Flexi**Chef[®] smart cooking. smart cleaning.



The new FlexiChef[®] – Your all-rounder in the kitchen!



Cooking

Perfect for soups, stews or pasta. Optimised, gentle cooking processes ensure top food quality

Grilling/Shallow Frying Perfect for preparing meat, fish or vegetables; even heat distribution



ReadyXpress[®] (Option) High speed cooking in FlexiChef[®] accelerates kitchen processes significantly

FlexiZone®



Divide the pan in up to three zones using the FlexiZone® feature. Each zone can be individually controlled.





Sous vide cooking

Cooking in vacuum sealed plastic bags

150

Soll 00h:05n

00h:05m

90 %

0

50

80 %

0

٥

Intelligent operating system – Fast. Large. Clearly arranged.

The new MagicPilot Intuitive operation and a perfect overview

- Faster hardware caters for a smoother workflow
- User friendly handling uniform control display for diverse **MKN** appliances

Guided Cooking – User navigation through the cooking process

- Automatic cooking processes
- Food quality can be reproduced fast and safely
- Useful notes as instructions; integration of photos possible
- Automatic control functions for perfect quality during cooking





* compared to previous MKN technology ** compared to conventional MKN pressure cooking equipment *** compared to conventional MKN technology *** optional in FlexiChe®

SpaceClean[®] – The first and only fully automatic cleaning system for pans*



Easier to operate

Orbital cleaning head tightly integrated in the lid



Faster

Set-up procedure not required



Faster amortisation

Up to 90%**less water consumption

Only 26 I water per cleaning cycle

*Option ** when using SpaceClean® compared to manual cleaning of conventional cooking equipment



SmartBoiling – the new energy efficient boiling process

| | standard cooking appliance | FlexiChef® (SmartBoiling) |
|---------------------------|-------------------------------|------------------------------|
| Energy consumption | 7 kWh | 0.2 kWh |
| Costs per 30 ct/kWh | 2.10€ | 0.06 € |
| Evaporated water | 13 litres | 0 litres |
| CO ₂ emissions | 2.9 kg | >0.1 kg |

Discover the next generation of cooking with SmartBoiling. With impressive **energy savings of 99%** compared to conventional boiling, SmartBoiling sets new standards in your kitchen.

Energy consumption - SmartBoiling vs. conventional boiling process. Figures refer to a 20 minute boiling process for 75 litres water. *compared to conventional boiling

Top quality for efficiency and a long lifespan

More sustainability

New ways of thinking. The new MKN FlexiChef[®] paves the way for groundbreaking and sustainable practices in cooking. Uncompromising quality, innovative features and an impressive package of user benefits, with the chef always in focus.

GreenHighlights in the new FlexiChef®

Innovation and sustainability combined in perfection



New lifting system in FlexiChef^{®*} Frying baskets can be lifted easily and safely out of the pan and set aside.

Benefits:

- Ergonomic design = safety for the user
- Easy and safe lifting of heavy/hot baskets
- 20% lighter baskets when fully loaded as by other systems
- Guaranteed success: perfectly cooked food due to automatic lifting of baskets at precisely the right time



* Optional accessories required

The future of digital commercial kitchens

WLAN*: Standard feature now

OPC UA interface

Connection to kitchen control system DIN 18898 (via OPC UA interface, open standard)

REST API interface

Connection with your own platforms and external platforms possible with Rest-API/Swagger interface

Software updates using cloud or app

* in all certified countries



FlexiZone®

Grilling/shallow frying, cooking or deep frying on up to three zones which can be operated separately. Energy is only used where required.



Turbo PowerBlock

- Optimal energy management due to extensive sensor technology in pan botto
- Energy is supplied only where needed
- Excellent heat storage properties
- Works well together with energy optimisation systems
 - Robust and durable, easy replacement of components

GreenInside consumption display

The MKN FlexiChef[®] has a consumption display^{*} that shows the energy and water consumption after each cooking process.

The new MKN FlexiChef®

Product overview and technical data

| FlexiChef® | Size 1 (50 I) | Size 2 (75 I) | Size 2 (100 l) | Size 3 (100 l) | Size 3 (150 l) | | | | | |
|--|---|-----------------|-----------------|------------------|-----------------|--|--|--|--|--|
| Dimensions | | | | | | | | | | |
| Length: mm | 1100 1300 | | 1300 | 1600 | 1600 | | | | | |
| Carcass width: mm | 850 | 850 | 850 | 850 | 850 | | | | | |
| Carcass height: mm | 750 | 750 | 750 | 750 | 750 | | | | | |
| Connection module | Optional connection to MKN OPTIMA 850 possible, additional space not required | | | | | | | | | |
| Connections | | | | | | | | | | |
| Electric 400 V | | | | | | | | | | |
| Electric load MaxPower: kW | 14.7 | 22.4 | 22.4 | 34.0 | 34.0 | | | | | |
| Electric load FlexPower: kW | 13.1 | 17.2 | 17.2 | 26.2 | 26.2 | | | | | |
| For 380 - 415 V | | | | | | | | | | |
| Fuse protection MaxPower: A | 35 | 50 | 50 | 63 | 63 | | | | | |
| Fuse protection FlexPower: A | 25 | 32 | 32 | 50 | 50 | | | | | |
| Mains / Frequency | 3 (N)PE AC / 50 Hz or 60 Hz | | | | | | | | | |
| Residual current device (RCD) | Recommended fuse protection (provided by customer), type A, 300 mA | | | | | | | | | |
| Feed water / waste water | | | | | | | | | | |
| Cold water (drinking water) | Volume flow min. 13 l/min, pressure 2-6 bar, | | | | | | | | | |
| Warm water (drinking water max. 60°C) | water hardness: < 4.5 mmol/l, dimensions 3/4" AG, DN 20 | | | | | | | | | |
| Waste water (drain water) | max 80°C, volume flow max 50l/min (fixed connection) or max. 70l/min (floor drain), DN 50 | | | | | | | | | |
| Skillet pan | | | | | | | | | | |
| Dimensions: mm | 523 x 543 x 225 | 723 x 543 x 225 | 723 x 543 x 315 | 1023 x 543 x 225 | 1023 x 543 x 31 | | | | | |
| Nominal capacity: I | 50 | 75 | 100 | 100 | 150 | | | | | |
| Max. oil capacity: I | 25 | 35 | 35 | 49 | 49 | | | | | |

Optional equipment

Hanging system for baskets

- Frying basket
- Cooking basket

Hanging system for GN containers

- GN container (unperforated)
- GN container (perforated)

- Shelf

- Ladle (unperforated)
- Ladle (perforated)
- Spatula for draining
- Straining sieve
- Wiper
- Pan scraper
- Cleaning brush
- Barcode scanner

- Shelf unit between Team appliances
- Transport trolley for GN containers
- Portable oil filtration system 75 I (230 V)
- Oil filter papers
- (50 pieces per box)
- Care & Protection

| FlexiChef [®] Team | Sizes 1 + 1 | Sizes 2 + 2 | Sizes 3 + 3 | Sizes 1 + 2 | Sizes 1 + 3 | Sizes 2 + 3 | | | |
|--|---|--|--------------------|-------------------|---------------------|-------------|--|--|--|
| Dimensions | | | | | | | | | |
| Length: mm | 2200 | 2600 | 3200 | 2400 | 2700 | 2900 | | | |
| Carcass width: mm | 850 | 850 | 850 | 850 | 850 | 850 | | | |
| Carcass height: mm | 750 | 750 | 750 | 750 | 750 | 750 | | | |
| Connection module | Optional connection to MKN OPTIMA 850 possible, additional space not required | | | | | | | | |
| Connections | | | | | | | | | |
| Electric 400 V | | | | | | | | | |
| Electric load MaxPower: kW | 14.7 + 14.7 | 22.4 + 22.4 | 34.0 + 34.0 | 14.7 + 22.4 | 14.7 + 34.0 | 22.4 + 34.0 | | | |
| Electric load FlexPower: kW | 13.1 + 13.1 | 17.2 + 17.2 | 26.2 + 26.2 | 13.1 + 17.2 | 13.1 + 26.2 | 17.2 + 26.2 | | | |
| For 380 - 415 V | | | | | | | | | |
| Fuse protection MaxPower: A | 35 + 35 | 50 + 50 | 63 + 63 | 35 + 50 | 35 + 63 | 50 + 63 | | | |
| Fuse protection FlexPower: A | 25 + 25 | 32 + 32 | 50 + 50 | 25 + 32 | 25 + 50 | 32 + 50 | | | |
| Mains / Frequency | 3 (N)PE AC / 50 Hz or 60 Hz | | | | | | | | |
| Residual current device (RCD) | Recommended fuse protection (provided by customer), type A, 300 mA | | | | | | | | |
| Feed water / waste water | | | | | | | | | |
| Cold water (drinking water) | Volume flow mi | n. 13 l/min, pres | sure 2-6 bar, | | | | | | |
| Warm water (drinking water max. 60°C) | water hardness: < 4.5 mmol/l, dimensions 3/4" AG, DN 20 | | | | | | | | |
| Waste water (drain water) | max 80°C, volu | me flow max 50 | l/min (fixed conne | ection) or max. 7 | Ol/min (floor drair | n), DN 50 | | | |
| Skillet pan | | | | | | | | | |
| Dimensions: mm | See dimensions | See dimensions of the FlexiChef [®] single units! | | | | | | | |
| Nominal capacity: I | 50 + 50 | 75 + 75 | 100 + 100 | 50 + 75 | 50 + 100 | 75 + 100 | | | |
| Max. oil capacity: I | 25 + 25 | 35 + 35 | 49 + 49 | 25 + 35 | 25 + 49 | 35 + 49 | | | |

Optional equipment

You can optimize your FlexiChef[®] with a comprehensive range of accessories suitable for every kitchen. These are all geared to meet your requirements, from ladles to transport trolleys. Our packs are the perfect solution for optimizing diverse applications in any professional kitchen.

Starter pack

- Spatula for draining
- Wiper
- Shelves
- Ladles (perforated and unperforated)

Cooking pack

- Hanging system for baskets
- One set of cooking baskets

GN-Pack

- Hanging system for GN containers
- Transport trolley for portioning
- incl. GN 1/1 container
- Straining sieve

Deep fat frying pack

- Hanging system for baskets
- One set of frying baskets