



Combi steamer
SpaceCombi Team
Electric combi steamer SpaceCombi TEAM
MKN-No.: TKECOD6100

TKECOD6100

Features

- **MagicPilot** – touch and slide operating concept
robust, wear-free, capacitive true colour touch screen,
protected behind 3 mm hardened safety glass; display
cleaning mode
- **autoChef** – automatic cooking
- more than 250 preselected international cooking processes which can be individually modified
- more than 350 cooking processes can be saved
- overview of individual favourites on the start screen
- cooking process protection against modification/deletion
- adjustable language settings, full text search
- **Manual operation concept** with 12 cooking modes:
SoftSteaming, Steaming, ExpressSteaming, Convection,
CombiSteaming, Perfection, low temperature cooking, ΔT ,
Sous vide, humidification, baking and rest function
- StepMatic – up to 20 programme steps can be individually combined
- **ChefsHelp** – user information
Insertion of information into text and graphics where required during the cooking process
- **VideoAssist** – interactive user assistance with clips featuring professional chefs
- **WaveClean** – automatic cleaning system
- **SES** – Steam Exhaust System, steam extraction for safe operation
- **GreenInside** – energy consumption display
- **QualityControl** – consistent high quality; perfect results every time regardless of the load quantity
- **hygienic cooking chamber doors with triple glazing**
 - lower door handle is turned 180°, ergonomic design
 - right hand hinged door
 - Hygienic cooking chambers of corrosion resistant stainless steel
- ETHERNET interface

Accessories

- 2 hanging racks for lengthwise insertion as standard, each with 6 shelf inserts for GN 1/1, with tilt protection for containers, distance between insert levels 60 mm



Option


- Left hand hinged door
- Interface for connection to an energy optimization system according to DIN 18875 and potential free contact
- Rollers instead of the rear appliance feet
- Maintenance rollers for front appliance feet
- Installation kit for waste water without water mains
- Electrical connection (15.6 kW)
- Ready to plug in (for one or two electrical connections)
- **HoodIn** – integrated steam condensation with a level of efficiency of approx. 80%

Product safety





Combi steamer
SpaceCombi Team
Electric combi steamer SpaceCombi TEAM
MKN-No.: TKECOD6100



Please find detailed information at www.mkn.com/en/login

General installation interfaces

Interfaces provided on site

- Electricity connection (EA/EZ)
- Connection to cold water mains (KW/TWk)
- Soft water (EW/EWk)
- Waste water connection (A/A)
- Exhaust air (AL)

Dimensions (LxWxH) (mm)	550 x 860 x 1815
Housing material	1.4301
Net weight (kg)	215
Installation instructions; safety clearance in mm	
at the rear	50



Combi steamer
SpaceCombi Team
Electric combi steamer SpaceCombi TEAM
MKN-No.: TKECOD6100

TKECOD6100

Capacity	
Shelf inserts	6 + 6 (12)
2/3 GN (354 x 325 x 65 mm)	6 + 6 (12)
1/1 GN (530 x 325 x 65 mm)	6 + 6 (12)
Plates Ø 28 cm on regeneration racks	12 + 12 (24)
Meals per day	60 - 160

Electricity supply (400 V)	
Nominal power consumption (kW)	2 x 7.8
Voltage (V)	2x 400 2x 3 NPE AC
Fuse protection (A)	3 x 16 + 3 x 16
Frequency range (Hz)	2 x 50 / 2 x 60

Drinking water cold (KW/TWk)	
Water pressure (bar)	2 - 6
Connection size	DN 20 (G ¾" A)
Quality mmol/l (°dH)	< 4 (22.2)
Consumption cleaning (l)	17.7

Soft water (EW/EWk)	
Water pressure (bar)	2 - 6
Connection size	DN 20 (G ¾" A)
Quality mmol/l (°dH)	< 0.9 (5)
Consumption steaming (l/h)	7.5
Consumption combisteaming (l/h)	1.7
Consumption cleaning (l)	1.3

Waste water (A/A)	
Volume flow max. (l/min.)	10
Connection size	DN 40
Quality	max. 95 °C

According to DIN 2052 with a connection voltage of 400 V	
Operated without steam condensate hood	
Noise level (db (A))	< 65
Type of protection	IPX5



Combi steamer
SpaceCombi Team
Electric combi steamer SpaceCombi TEAM
MKN-No.: TKECOD6100

Further features

- **CombiDoctor** – self diagnosis programme
automatic self-test for all relevant appliance functions such as climate and cleaning functions
- **FamilyMix** – efficient utilization of the cooking chamber capacity. Products which can be cooked in the same cooking chamber climate are indicated in a clearly arranged list showing which products belong together.
- one hand door handle
- non-contact door switch, door lock positions with end stop
- insertable door seal – end user replaceable
- drip pan with permanent drainage
- LED lighting integrated into the hygienic cooking chamber door
- **DynaSteam** – dynamic process-oriented steam quantity adjustment depending on product load
- autoreverse fan for extremely uniform cooking results
- 5 fan speeds programmable, even 10 speeds in connection with fan intervals
- fan safety brake
- manual cleaning programme with user guide
- maintenance instructions for external water filters
- **Time2Serve** – enter the required completion time
- **RackControl** – multiple timer
- **ClimaSelect plus** – Climate control in steps of 10 %
- **Ready2Cook** – preheating, cooling down, climate preparation
- **PerfectHold** – keep warm function with SmartCoolDown
- internal multipoint core temperature measurement (up to 99 °C)
- **EcoModus** – reduces temperature of cooking chamber automatically when it has not been charged for some time
- energy supply as required, reduced heat output (E/2)
- **MKN CombiConnect** – PC software equipped as standard to compile cooking programmes
- integrated HACCP memory
- **Professional baking function** – to set baking programmes with humidity injection in ml, a rest period and dehumidification
- manual steam injection/humidification
- timer with start time pre-selection and real time display
- start cooking process with **BarcodeScan** in autoChef
- USB interface, e.g. for software updates**
- cooking process import function using a USB stick
- display flashes after cooking time has elapsed
- loudspeaker, adjustable tone control
- audible signal after cooking time has elapsed
- potential free contact for external steam condensate hood
- direct waste water connection according to DVGW is possible
- siphon is included with the appliance

** without surcharge under www.mkn.com

Special equipment

1/1 GN trays (please refer to accessories brochure)

10012901	Frying basket
202345	Granite enamelled tray, 20 mm deep
202379	Baking tray – perforated
206104	Grid
202375	Cup baking tray

10014181	Barcode scanner including USB cable for charging
10012974	WaveClean two-in-one cleaning cartridge
817382	Hanging racks 5 x GN 1/1, distance between insert levels 65 mm

