

## DV125.2

Execution for: Denmark

### Utensil washing machine

Working direction: left - right

Working height: 850 mm

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3°dH



Sample illustration

© MEIKO 2016

### Technical data

<b>Rack capacity/h (theoretical)</b>	60 / 40 / 17 racks/h
<b>Programme cycle</b>	60 / 90 / 210 s
<b>Rack dimension</b>	500 x 500 mm (650 x 500)
<b>Entry height</b>	555 mm
<b>Dimensions (W x H x D)</b>	735 ( 789) x 1590 x 750 (850) mm (with hood rod)
<b>Electrical feeding cable</b>	3-phase current: 3N PE 400V 50Hz Total connected load: 12,7 kW max. rated current: 25,0 A
<b>Protection class of the machine</b>	IP X5
<b>Equipment</b>	MIKE 2 control Infrared interface for wireless communication Leakage detector Soft start Boiler safety device Drain pump Automatic self-cleaning when tank is drained Aqua-Stop system Hood start
<b>Fresh water line</b>	Air gap 'AA' in accordance with EN 1717 with booster pump
<b>Fresh water supply</b>	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure 500 kPa / 5,0 bar Max. supply water temperature 60 °C
<b>Flow rate</b>	5 l/min
<b>Final rinse water quantity</b>	3,2 liters/cycle

# Technical Information

<b>Boiler</b>	Contents: 10,5 l Heater: 9,00 kW Temperature: 83 °C
<b>Wash tank</b>	Filling: 26,0 l Heater: 2,00 kW Temperature: 60 °C, adjustable of 10 - 80 °C
<b>Wash pump, with frequency converter</b>	Performance: 1,50 kW
<b>Dosing of rinse aid</b>	Hose pump (24 V) with time control and suction lance
<b>Material</b>	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
<b>Heat emission</b>	for 25 programme cycles/h total: 2,7 kW perceptible: 1,8 kW latent: 0,9 kW
<b>Ventilation flow rate</b>	680 m <sup>3</sup> /h
<b>Steam emission</b>	1,3 kg/h
<b>Sound level</b>	66 dB(A)
<b>Net weight</b>	130,0 kg