TRUE REFRIGERATION ® INTERNATIONAL

UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com





11/21

Model:

TUC-60D-2-HC

Undercounter:

Drawered Refrigerator with Hydrocarbon Refrigerant





TUC-60D-2-HC

- True's undercounter units are designed with enduring quality that protects your long term investment.
- Factory engineered system using environmentally friendly R290 hydro carbon refrigerant maintains temperature of 0.5°C to 3.3°C for the best in food preservation.
- Exterior stainless steel front, top and ends. GalFan coated steel back.
- Interior NSF approved, clear coated aluminum liner. Stainless steel floor with coved corners.
- Front breathing.
- Each drawer accommodates one (1) 1/1GN (W 530mm x D 325 x H 150 mm) food pan (sold separately).
- Foamed-in-place using a high density, environmentally friendly polyurethane insulation.

NOTE: Door or drawer assemblies can be located in any section of the cabinet. Location of doors/drawers must be indicated at time of ordering.

PLAN VIEW





ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next $\mathcal{V}^{"}$).

	Voltage: 220-240V/50-60Hz		Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8").											
			Doors/		Cabinet Dimensions (mm)			Net Volumes			24 hr/ Energy Consump-	Annual Energy Consump-	Crated Weight	
	Model	Model Type	Drawers	Shelves	W	D†	Н	(litres)	EEC	EEI	tion (kWh)	tion (kWh)	(kg)	
	TUC-60D-2-HC	Counter Chilled	1/2	2	1534	766	839	226	В	31,5	2,045	746	157	

[†] Depth does not include 26 mm for rear bumpers.

Test Standard: EN16825 - Climate Class 5 (40°C, 40% relative humidity).