## TRUE REFRIGERATION © INTERNATIONAL

UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Australia Tel +61 2 9618 9999 • www.truemfg.com 5/21

Model: TUC-60D-4-HC

## Undercounter:


Drawered Refrigerator with Hydrocarbon Refrigerant




## TUC-60D-4-HC

- True's undercounter units are designed with enduring quality that protects your long term investment.
- ▶ Factory engineered system using environmentally friendly R290 hydro carbon refrigerant maintains temperature of 0.5°C to 3.3°C for the best in food preservation.
- Exterior stainless steel front, top and ends. GalFan coated steel back.
- Interior NSF approved, clear coated aluminum liner. Stainless steel floor with coved corners.
- Front breathing.
- Each drawer accommodates one (1) 1/1GN (W 530mm x D 325 x H 150 mm) food pan (sold separately).
- Foamed-in-place using a high density, environmentally friendly polyurethane insulation.

## PLAN VIEW





| ROUGH-IN DATA             |   |                 | Specifications subject to change without notice.<br>Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next 1/8"). |         |      |     |     |          |     |                           |                              |                  |     |  |
|---------------------------|---|-----------------|--|---------|------|-----|-----|----------|-----|---------------------------|------------------------------|------------------|-----|--|
| Voltage: 220-240V/50-60Hz |   |                 | Chart dimensions rounded up to the next whole minimizer (inclus rounded up to the next %).   |         |      |     |     |          |     |                           |                              |                  |     |  |
|                           |   |                 | Cabinet Dimensions<br>(mm)   |         |      |     | Net |          |     | 24 hr/ Energy<br>Consump- | Annual<br>Energy<br>Consump- | Crated<br>Weight |     |  |
| Model                     |   | Model Type      | Drawers  | Shelves | W    | D†  | н   | (litres) | EEC | EEI                       | tion (kWh)                   | tion (kWh)       |     |  |
| TUC-60D-4-H               | С | Counter Chilled | 0/4  | _       | 1534 | 766 | 839 | _        | _   | 27,2                      | 2,04                         | 746              | 186 |  |

† Depth does not include 26 mm for rear bumpers.

Test Standard: EN16825 - Climate Class 5 (40°C, 40% relative humidity).