

PRODUCT CONFIGURATION

Actuator LA40.

Item No: J13186
Item Name: 400502000A0M0B26+12DB137342000
Protection Class: IPx6
Load Type: Push
Load: 4000 N
Self Lock: 4000 N
Speed: 6.8 mm/s
Gear Ratio: 01:42
Brake: Yes
Stroke length: 200 mm.
Installation Dimension: 373 mm.
Special Installation Dimension: Yes
Voltage: 33 V
Colour: Grey (RAL 7035)
Fire category : V2
Safety Factor: 2.0
Safety Nut: Yes
Spline: None
QuickRelease: None
Platform: None
End-Stop Type: Encoded
Feedback : Dual Hall Encoded
Piston Rod Eye: With Slot, $\varnothing 10.2$, Steel
Bushing: Yes
Back Fixture: WithSlot, $\varnothing 10.2$, Plastic, Orientation: 90°



Terms of use

The user is responsible for determining the suitability of LINAK products for specific application. LINAK takes great care in providing accurate and up-to-date information on its products. However, due to continuous development in order to improve its products, LINAK products are subject to frequent modifications and changes without prior notice. Therefore, LINAK cannot guarantee the correct and actual status of said information on its products. While LINAK uses its best efforts to fulfil orders, LINAK cannot, for the same reasons as mentioned above, guarantee the availability of any particular product. Therefore, LINAK reserves the right to discontinue the sale of any product displayed on its website or listed in its catalogues or other written material drawn up by LINAK. All sales are subject to the Standard Terms of Sale and Delivery for LINAK. For a copy hereof, please contact LINAK

LINAK® 
WE IMPROVE YOUR LIFE

PLEASE SEE THE RELEVANT DATA SHEET OR USER MANUAL ON OUR WEBSITE WWW.LINAK.COM