

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Bartscher Chafing fuel
- · UFI-Code: G800-P0VS-K00F-T4YR
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Chafing fuel
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bartscher GmbH Franz-Kleine-Str. 28 33154 Salzkotten www.bartscher.de

· Informing department:

Tel: +49(0)5258-971-0 Fax: +49(0)5258-971-120

· 1.4 Emergency telephone number:

Giftnotruf Berlin

Tel. +49 (0)30 30686 700

Helpdesk in German and in English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Sol. 1 H228 Flammable solid.



Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

(Contd. from page 1)

· Hazard statements

H228 Flammable solid.

H319 Causes serious eye irritation.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from open flames. - No smoking.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Ethanol-containing burning paste solidified by a gelling agent.

· Dangerous components:		
CAS: 64-17-5	ethanol	50 - 100%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-0372		
CAS: 67-56-1	methanol	≥ 0.1 - < 2.5%
EINECS: 200-659-6	♦ Flam. Liq. 2, H225; ♦ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;	
Reg.nr.: 01-2119433307-44-X		
	♦ STOT SE 1, H370	

· Additional information

All ingredients are registered according to REACH-regulation. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact

Remove contaminated clothing.

Rinse with warm water.

If skin irritation continues, consult a doctor.

· After eye contact

Keep eye lids open and rinse them with ample amounts of clean running water for at least 15 minutes.

Seek medical treatment.

- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Extinguishing powder, foam or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- \cdot 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

(Contd. on page 3)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

(Contd. from page 2)

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

In case of fire wear breathing equipment being independent of ambient air and suit provided full protection against chemicals.

· Additional information Cool endangered containers with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Avoid contact with the product.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binders) and disposal in suitable containers.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Avoid contact with eyes and skin.

First, put the can with the burning paste in the holding device or below the heater before igniting it. Let the can burn off only when standing vertically.

Keep it away from inflammable materials, e.g. tablecloths and decorating papers.

Keep out of the reach of children.

· Information about protection against explosions and fires:

Store it away from ignition sources or open fire.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Store only in the original container.

Keep container tightly closed.

Ensure sufficient ventilation.

Store in cool location.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Keep away from strong oxidizing, alkalis and acidic materials.

- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with limit values that require monitoring at the workplace:

WEL: workplace exposure limit

64-17-5 etha	ınol
--------------	------

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 4)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

	(Contd. from page 3)
67-56-1 methanol	
WEL (Great Britain)	Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk
IOELV (European Union)	Long-term value: 260 mg/m³, 200 ppm Skin

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment
- Breathing equipment: Use breathing protection in case of insufficient ventilation.
- · Protection of hands:



Protective gloves.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Nitrile rubber, NBR

· Eye protection:



Tightly sealed safety glasses.

· Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:gelColour:Colourless• Odour:alcohol-like

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: 79 °C

· Flash point: 16 ℃

· Inflammability (solid, gaseous) Highly flammable.

· **Self-inflammability:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower: 3.3 Vol %

(Contd. on page 5)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

	(Contd. from page 4)
Upper:	19 Vol %
· Vapour pressure at 20 ℃:	59 hPa
· Density at 25 ℃	0.84 g/cm³
Solubility in / Miscibility with Water: 9.2 Other information	Dispersible No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation

More frequent and continuous contact with the skin may result in irritation of the skin.

Serious eye damage/irritation

Irritation in case of direct contact

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 6)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

(Contd. from page 5)

- · **vPvB**: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Ensure cans are completely empty before recycling.

Let the boxes burn off completely and dispose of them in the collection of recyclable materials depending on municipal regulations.

· European waste catalogue		
07 00 00	00 WASTES FROM ORGANIC CHEMICAL PROCESSES	
07 01 00	07 01 00 wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals	
07 01 04*	other organic solvents, washing liquids and mother liquors	
15 00 00	15 00 00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AN PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED	
15 01 00	15 01 00 packaging (including separately collected municipal packaging waste)	
15 01 04	metallic packaging	

- · Uncleaned packagings:
- · Recommendation:

Empty containers are to be introduced to the scrap processing and/or to the reconditioning. Packing drums which are not duly emptied belong to hazardous waste.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1325
· 14.2 UN proper shipping name	
· ADR · IMDG	1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (ETHANOL (ETHYL ALCOHOL)) FLAMMABLE SOLID, ORGANIC, N.O.S. (ETHANOL (ETHYL ALCOHOL))
· IATA	FLAMMABLE SOLID, ORGANIC, N.O.S. (ETHANOL)

- · 14.3 Transport hazard class(es)
- · ADR



• Class 4.1 (F1) Flammable solids, self-reactive substances and solid desensitised explosives.

(Contd. on page 7)

Printing date 29.03.2018 Version number 5 Revision: 29.03.2018

Trade name: Bartscher Chafing fuel

	(Contd. from page 6)
· Label	4.1
· IMDG, IATA	
· Class · Label	4.1 Flammable solids, self-reactive substances and solid desensitised explosives.4.1
· 14.4 Packing group · ADR, IMDG, IATA	II
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable solids, self-reactive substances and solid desensitised explosives.
Kemler Number:EMS Number:Stowage Category	40 F-A,S-G B
 14.7 Transport in bulk according to Ann of Marpol and the IBC Code 	nex II Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category 	1 kg Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g 2
· Tunnel restriction code	E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1 kg Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
· UN "Model Regulation":	UN 1325 FLAMMABLE SOLID, ORGANIC, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 4.1, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I methanol
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 40
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Substances of very high concern (SVHC) according to REACH, Article 57

 None of the ingredients is contained.

(Contd. on page 8)

Version number 5 Revision: 29.03.2018 Printing date 29.03.2018

Trade name: Bartscher Chafing fuel

(Contd. from page 7)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H370 Causes damage to organs.

Department issuing data specification sheet:

This Material Safety Data Sheet has been drawn up in cooperation with:

DEKRA Assurance Services GmbH, Hanomagstr. 12, D-30449 Hanover, Germany,

phone: (+49) 511 42079 - 0, reach@dekra.com.

© DEKRA Assurance Services GmbH. Changing this documents is subject to explicit acceptance by DEKRA Assurance Services GmbH.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2

Flam. Sol. 1: Flammable solids – Category 1 Acute Tox. 3: Acute toxicity – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

· * Data compared to the previous version altered.