

**MANUFACTURER**

HALLDE

MODEL

RG-200

PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 7 kg/minute.

ORIGIN

Sweden

SPECIFICATION

SPECIFICATION TEXT	Vegetable preparation machine with leaning design and full moon feed cylinder, made to process 7 kg/minute or 50-700 portions/day. Machine has aluminium pusher plate with aluminium handle and a tube feeder of 56 mm in diameter. Three litre feed cylinder. Cutting tools are made of stainless steel/aluminium/acetal with removable knives/plates and are 185 mm in diameter. Motor rotate the cutting blade clockwise and direct without intermediate belts.				
FUNCTION	Machine for slicing, dicing, shredding, grating and cutting julienne. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.				
CAPACITY	Up to 700 portions/day and up to 7 kg/minute. 3 liter feed cylinder, 56 mm tube feeder for elongated products.				
MATERIAL	Machine base, feed cylinder and pusher plate: aluminium alloy. Cutting tools: stainless steel/aluminium/fiberglass reinforced polyamide. Ejector plate: acetal.				
MOTOR	0.25 kW. One-speed (350 rpm) 100 V, 1-phase, 50/60 Hz. 110-120 V, 1-phase, 60 Hz. 220-240 V, 1-phase, 50/60 Hz. Thermal protection, Planetary gearing.				
POWER SUPPLY	Earthed, single phase / three phase.				
STANDARDS	EN 1678+A1:2010. NSF/ANSI Standard 8.				
RECOMMENDED CUTTING TOOL PACKAGES	INCLUDING				NET WEIGHT
	<ul style="list-style-type: none"> • 4-pack Cutting Tools <ul style="list-style-type: none"> - Slicer 1.5 mm - Slicer 4 mm - Grater/Shredder 2 mm - Grater/Shredder 4 mm 				2 kg
	<ul style="list-style-type: none"> • 7-pack Cutting Tools <ul style="list-style-type: none"> - Slicer 1.5 mm - Slicer 4 mm - Slicer 10 mm - Grater/Shredder 2 mm - Grater/Shredder 8 mm - Julienne Cutter 4x4 mm - Dicing Grid 10x10 mm 				3,5 kg
WEIGHT/VOLUME	CONTENT	NET WEIGHT	PACKAGES	FREIGHT WEIGHT	FREIGHT VOLUME
	RG-200 Machine	18.6 kg	1	19 kg	0.077 m ³
	Container Trolley incl. GN 1/1 container	9 kg	1	12.5 kg	0.15 m ³
	Machine Table incl. GN 1/1 container	13,25 kg	1	14,5 kg	0,8 m ³
SAFETY	2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011, 1935/2004CE, SS-EN ISO 26800:2011.				
DIRECTIVE AND REGULATION	CE approved. Two safety switches, machine safety: IP44, push buttons safety: IP65.				

DRAWINGS

The drawings below can be downloaded at hallde.com.

