





MANUFACTURER

HALLDE

MODEL

RG-250 diwash

PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 10 kg/minute.

ORIGIN

Sweden

	S	PECIFICATION			
SPECIFICATION TEXT	Vegetable preparation machine with leaning design and full moon feed cylinder, made to process up to 10 kg/minute or 1000 portions/day. The machine's pusher plate, knife housing and feed piston are made of aluminium and have an organic polymer coating. The organic coating allows these parts to be cleaned in a dishwasher, "diwash". The pusher plate has a loop-shaped, stainless steel handle and a 56-mm diameter feeder tube. Pusher plate with system for leverage effect. Four-litre feed cylinder with 55 mm inner wall. All removable parts of the RG-250 diwash are dishwasher safe. The associated cutting tools are 185-mm in diameter, made of stainless steel/aluminium/acetate, have exchangeable knives/plates and are dishwasher safe. The motor rotates the cutting blade clockwise and directly, without intermediate belts.				
FUNCTION	Machine for slicing, dicing, shredding, grating, cutting julienne and French fries. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.				
CAPACITY	Up to 1000 portions/day and up to 10 kg/minute. 4 liter feed cylinder, 56 mm tube feeder for elongated products.				
MATERIAL	Machine base: aluminium. Knife housing, feed cylinder and feed piston: aluminium with organic, polymer coating. Handle: stainless steel. Cutting tools: stainless steel/aluminium/fibreglass-reinforced polyamide. Ejector plate: acetate.				
MOTOR	0.55 kW. One-speed (350 rpm) 120 V, 1-phase, 60 Hz. 220-240 V, 1-phase, 50/60 Hz. 230-240 V, 3-phase, 50 Hz. 400 V, 3-phase, 50/60 Hz. 440 V, 3-phase, 60 Hz. Thermal protection, Planetary gearing.				
POWER SUPPLY	Earthed, single phase / three phase.				
STANDARDS	EN 1678+A1:2010. NSF/ANSI Standard 8.				
RECOMMENDED CUTTING TOOL PACKAGES	INCLUDING				NET WEIGHT
	4-pack Cutting Tools Slicer 1.5 mm				2 kg
	• 7-pack Cutting Tools - Slicer 1.5 mm - Grater/Shredder 2 mm - Julienne Cutter 4x4 mm - Slicer 4 mm - Grater/Shredder 8 mm - Dicing Grid 10x10 mm - Slicer 10 mm				3,5 kg
WEIGHT/VOLUME	CONTENT	NET WEIGHT	PACKAGES	FREIGHT WEIGHT	FREIGHT VOLUME
	RG-250 diwash Machine	22 kg	1	25 kg	0.183 m³
	Container Trolley incl. GN 1/1 container	9 kg	1	12.5 kg	0.15 m³
	Machine Table incl. GN 1/1 container	13,25 kg	1	14,5 kg	0,8 m³
SAFETY	2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011, 1935/2004CE, SS-EN ISO 26800:2011.				
DIRECTIVE AND REGULATION	CE approved. Two safety switches, machine safety: IP44, push buttons safety: IP65.				

